



ZORROfix

FOR CONSTRUCTION PROFESSIONALS

WATERPROOFING & CONSTRUCTION CHEMICALS



ZORROPROOF | 007L

Liquid waterproofing product

LIQUID INTEGRAL WATERPROOFING COMPOUND FOR CONCRETE AND MORTAR

Areas of Application:

Water reducing and waterproofing admixture for all types of concrete and mortar. It is used for waterproofing of concrete and sand cement mortar used in basements roof slabs, screeds, water retaining structures, beams, columns, culverts, tunnels, sunken slabs, terrace slabs, water tanks, sewerage works etc.

Features and Benefits:

- Being a liquid it is easily dispersible & compatible with concrete/mortar mixes
- Increases workability of the concrete mix without increased water content
- Compatible with all varieties of Portland cement including Slag Cement
- To be added to gauging water before adding to the mix & requires a very small dosage hence convenient to handle and great money saver
- Increases cohesive property of concrete / mortars thus eliminating segregation and bleeding
- Minimizes porosity & capillary action
- Reduces rebound loss
- It reduces the permeability of water into concrete
- Reduces shrinkage & crack development in concrete and plasters
- No added chloride

Packaging:

ZORROPROOF 007L is available in 200 ml, 1 ltr, 5 ltr, 10 ltr, 20 ltr, 50 ltr & 200 ltr.

Dosage:

200 ml for 50 kg bag of Cement.



ZORROCRETE | 008W

Waterproofing & repair product

ZORROCRETE 008W IS STYRENE BUTADIENE RUBBER BASED BONDING AGENT

Areas of Application:

For waterproofing of Roof Slabs, Sunken Slabs, Basements, Water Tanks, Balconies, Sunshades etc. It is used as a Bonding Agent between old & new concrete for cementitious substrates. It is also effective to make repair mortars & concrete in building rehab work. Treatment for leaching & salt petre action. It is multipurpose mortar admixture for injection grouts.

Features and Benefits:

- White turbid liquid can be easily applied by brush
- Provides excellent bond to concrete, adhesion plaster, masonry, stone work, etc.
- Strengthening cold joints between old and new concrete, making them non-permeable
- Multi purpose use as a bonding agent, modifier for cement-sand & concrete mixes in building repairs
- Gives weather resistant mortar with improved durability & impermeability against chlorides and other harmful agents
- Excellent as a cement modifier
- It prevents cracking by improving flexural strength
- Allows breathing thus preventing peeling off
- Repair mortar modified with ZORROCRETE 008W is suitable for repairing of RCC beams, columns, slabs and other RCC members
- Reduces shrinkage & water permeability in concrete & mortar
- Good as a bonding agent in repairs & renovations
- Reduces chloride/salt penetration in Marine environment
- Compatible with all common hydraulic cements

Packaging:

500 gm, 1 kg, 5 kg, 10 kg, 20 kg, 50 kg & 200 kg



Coverage / Dosage:

Application	Ratio	Coverage
As a passivator Coat	1:1 (Zorrocrete 008W:Cement)	2-3 Rmtr/kg for 25mm dia bar at 1 mm thickness.
As a Waterproof Coating	1:1.5 (Zorrocrete 008W: Cement)	16-21 Sq. ft for 2 coat at 0.5-0.6 mm thickness
As Bonding Coat	1:1 (Zorrocrete 008W: Cement)	21-32 Sq. ft

ZORROCRACKFIX | 009C

Crack filler

READY TO USE PASTE FILL CRACKS FOR INTERNAL & EXTERNAL SURFACES IN PLASTER

Areas of Application:

Repairing of internal and external cracks in plastered surfaces up to 5 mm X 5 mm size. Suitable for both vertical and horizontal applications wherever hairline cracks are observed. It can be used for leveling the undulations of the un-plastered or plastered ceilings & walls before painting.

Features and Benefits:

- Easy to apply by putty knife similar to conventional putties
- Accommodates slight movements in the cracks
- No Shrinkage & Non staining
- Single component
- For both internal and external surfaces
- Over-coatable by any type of water based paints after 24 hours
- For cracks in cement plaster upto 5 mm wide
- UV and water resistant
- It can be used as putty on plastered surfaces in patch works
- It can be tinted by using water based stainers
- Excellent adhesion
- Can be applied on damp surfaces but not on cracks with running water

Packaging:

500 gm, 1 kg & 5 kg

Coverage:

Approx. 25 RMT/kg for 5 mmX5 mm crack depending on site conditions.



ZORROCRETE | 010AP

Waterproofing & repair product

ACRYLIC MODIFIER

Areas of Application:

Waterproofing of terrace, toilets, chajja, masonry walls, sloping RCC roofs, etc. For making polymer mortar for repairs mortars etc. As a bonding agent on cold/construction joints. Multipurpose mortar admixture for injection grouts. Treatment of leaching & salt pater action. Additive to cement based paints for waterproofing.

Features and Benefits:

- Good bonding properties
- Good as a waterproof coating
- Static cracks can be filled with mortar made with ZORROCRETE 010AP
- A good modifier to make repair mortar/concrete
- Durable to UV exposure
- Eco-friendly

Packaging:

500 ml, 1 litr, 5 litr, 20 litr, 50 litr & 200 litr.

Coverage:

15-20 sq.ft/litr for 2 coats. (ZORROCRETE 010AP+Cement in the proportion 1:2)



ZORROCRETE | 2K011

Waterproofing & repair product

TWO COMPONENT READY TO USE ACRYLIC BASED WATERPROOF COATING SYSTEM

Areas of Application:

Water Tanks, Roof slabs, Terraces, Balconies, Sunshades, Sunken Toilets Retaining Wall, Basements, Swimming Pools etc.

Features and Benefits:

- Elastomeric Coating with 40-50% elongation
- DFT: 1 mm, four times thicker than ordinary polymer cement coating
- Factory controlled & prepacked, consistent in quality
- Easy to apply by brush or in thin trowel applications
- Protects concrete against water penetration, chloride and carbonation
- Waterproof for concrete structure
- Flexible, bridges hairline cracks in concrete & plaster
- Non-toxic, good for potable water tanks
- Prebatched, no additional cement, sand and water required to make the slurry

Packaging:

3 kg & 15 kg

Coverage:

Approximately 6 to 7 Sq.ft/kg of mixed material in two coats with a thickness of 1 to 1.2 mm depending on the surface undulations.



ZORROFIX TILE GROUT | 012TG

Ready to use waterproof coloured tile joint filler

POLYMER MODIFIED CEMENTITIOUS GROUT FOR WALL AND FLOOR TILE JOINT

Areas of Application:

ZORROFIX TILE GROUT 012TG is a gap filling material between different wall and floor tiles like ceramic, glazed, vitrified, mosaic, glass mosaic and marble tiles etc. It effectively fills the gaps and levels itself to give hard wearing, non-dusting tile joints. It does not allow moisture and water to seep into the back of the tiles that causes dislocation. It holds the tiles firmly together to give them a long life.

Features and Benefits:

- Cementitious, only water to be added
- Excellent bond with tiles
- Non Shrinking-Occupies the filled space permanently without shrinking
- Waterproof
- Polymer based
- Easy to use and clean
- Non-dusting

Packaging:

1 kg.

Coverage:

Depends on tile size & joint width.



ZORROCLEAN | 013TC

Multipurpose stain remover

HIGH QUALITY DETERGENT BASED CLEANING & DEGREASING SOLUTION FOR MOSAIC, CERAMIC, GLAZED TILES, BATHTUBS, WASHBASIN, PRIVY BASIN & CONCRETE

Areas of Application:

ZORROCLEAN 013TC is a powerful but gently concentrated detergent based (mildly acidic) tiles cleaner for tiles, wash basin, bath tubs, privy basin and concrete etc. Rapid removal of white yellowish spot/layer along with water stains over tiles, cement stains, grime, oil, grease, paint stains, moss and wax from concrete asbestos & ceramics. Its unique formula is ideal for residential and commercial use

Features and Benefits:

- Removes the most stubborn stains easily
- Does not damage joint between ceramic tiles, even those grouted with coloured products
- Fast acting
- Does not effect glaze of tiles
- Excellent tolerance to hard water

Packaging:

500 ml & 1 lr

Coverage:

45-65 Sq.ft/ltr. depends on porosity & contamination of substrate.



ZORRO NEW SOLO COAT | 014NC

3-Coat waterproof coating for terraces

HEAVY DUTY DURABLE REINFORCED ACRYLIC WATERPROOF COATING FOR TERRACE

Areas of Application:

All new RCC flat and sloping roofs. Existing cementitious waterproofing treatments like brick-bat-coba, concrete screeds, acrylic coatings etc.

Features and Benefits:

- Better film thickness Provides 1 mm to 1.25mm dry film thickness in 3 coats
- High Crack bridging ability Bridges cracks upto 2 mm width
- No need to remove existing sound BB coba, plaster, concrete surface
- Can be used for flat as well as sloping roofs
- High tensile strength, tear resistance & bond strength with cementitious substrates as compared to available products
- No streeting required for normal foot traffic
- Good resistance- Against UV infrared rays, algal, fungal growth. Light in weight
- Easy in application- Can be applied by roller
- Non toxic, breathable & washable
- Aesthetic finish available in white colour
- Surface to be self primed with 50% dilution before application of coating

Packaging:

5 Kg & 20 K

Coverage:

1.80-2.00 mtr sq per kg per coat. (Coverage may vary depending upon surface condition.)



ZORROFIX TAP CLEANER | 015TC

Soap scum, dirt & grease cleaner

ZORROFIX TAP CLEANER IS A UNIQUE FORMULATION TO REMOVE SOAP SCUM, DIRT & GREASY PARTICLES

Areas of Application:

Kitchen Sinks, Bath Fittings, Plastic & Steel Fixtures, Bath Accessories, Bath Tubs etc. All types of Aluminum Fittings

Features and Benefits:

- Unique formulation
- Remove soap scum, dirt & greasy particles

Method of Application:

Spray few drops on the effected surface, wait for 30 to 60 seconds & rub the affected area with cotton cloth. Wipe the surface with clean cloth & rinse thoroughly with fresh water.

Packaging:

250 ml & 500 ml

Coverage:

Varies by applications



ZORROFIX EPOXY TILE GROUT | 016ETG

Epoxy resin based tile joint filler

ZORROFIX EPOXY TILE GROUT IS AN EPOXY RESIN BASED TILE JOINT FILLER

Areas of Application:

Filling tile joints in Terrace, Balconies, Kitchen, Pubs, Food plants, Restaurants, Hospitals, Chemical labs, Swimming pools, Toilets etc.

Features and Benefits:

- Anti-cracking, non-shrinking and withstands heavy traffic
- Stain, Dirt & Acid proof
- 100% Solid Epoxy Grout
- Excellent fungal and chemical resistance
- No water seepage
- Increased adhesion and reduced chalking

Packaging:

1 kg & 5kg

Coverage:

Contact local AIPL representative or call us today



ZORROFIX TILE ADHESIVE | 017CTA

Waterproof tile adhesive

ZORROFIX TILE ADHESIVE 017 CTA IS POLYMER MODIFIED CEMENT BASED POWDER TILE ADHESIVE

Areas of Application:

Quick set adhesive for fixing of Ceramics, Granite & Cement tiles. Damp and submerged services like toilets and kitchens. Its unique formula is ideal for residential and commercial use.

Features and Benefits:

- Ready to use, only water to be added
- Contains special chemicals to obtain non-shrink, waterproof & excellent adhesion properties
- Fast setting & quick strength development

Method of Application:

- The surface should be sound and thoroughly cleaned. Old surface should be free from any impurity
- Add 3 parts of Zorrofix Tile Adhesive 017 CTA powder to 1 part of water to get desired consistency
- Spread the adhesive to a required thickness bed and comb with a notched trowel. Strictly apply the adhesive paste which can be tiled within 10 to 15 min
- Apply the adhesive to the floor surfaces. Don't spread more than 1 sq.m at a time. Do not use in damp condition
- Start placing the tiles on the surface. Tap to ensure complete coverage
- Allow to set for 24 hours. Fill joints with Zorrofix Tile Grout



Packaging:

20 kg bag

Coverage:

Varies with applications.

ZORROFIX TILE ADHESIVE | 018VTA

Floor & wall thin set adhesive

ZORROFIX TILE ADHESIVE 018 VTA IS A FLOOR AND WALL THIN-SET ADHESIVE

Areas of Application:

Ready to use tile adhesive for fixing Vitrified, Ceramic & Mosaic tiles on Wall and Floor. This is an ideal product for Tile-On-Tile applications

Features and Benefits:

- Ready to use, only water to be added
- For External & Internal use
- Excellent stability & bonding strength
- Must for fixing tile on existing tile without removal of old tiles
- Superior Workability
- Ultra High Adhesion & Flexural strength
- Can use Thin & Thick bed

Method of Application:

- The surface should be sound and thoroughly cleaned. Old surface should be free from any impurity
- Add 3 parts of Zorrofix Tile Adhesive 018 VTA powder to 1 part of water to get desired consistency
- Consumed within 60 min pot life
- Spread the adhesive to a required thickness bed and comb with a notched trowel. Strictly apply the adhesive paste which can be tiled within 10 to 15 min
- Apply the adhesive to the floor surfaces. Don't spread more than 1 sq.m at a time. Do not use in damp condition
- Start placing the tiles on the surface. Tap to ensure complete coverage
- Allow to set for 24 hours. Fill joints with Zorrofix Tile Grout



Packaging:

20 kg bag

Coverage:

Varies with applications.



AIPL ZORRO PVT. LTD.

302, 3rd Floor, D-Mall, Netaji Subhash Place, Pitampura,

Opp. Wazirpur DTC Depot, Delhi-110034,

Tel: 011-49010190, Fax: 011-49010102

Mob.: 8448892000, Customer Care No.: 011-49010144

E-mail: info@aiplzorro.com | www.aiplabro.com | www.aiplzorro.com



TOLL-FREE NO
1800 27 40409